

TECHNICAL SHEET

VOODOO BOOMBOX



BASS REFLEX	CIRCULAR FRONT VENT
WAYS	2
SHELL MATERIAL	FLAX FIBER
WEIGHT / VOLUME	7 KG / 20 L
DIMENSIONS	40CM X 24CM X 22CM
AUTONOMY	15H
SEALING STANDARD	IP44
POWER	200 W RMS
FREQUENCY	45 TO 20 000 HZ
DISTORSION 90 DB LESS THAN 1 %	100 HZ TO 22 KHZ
SENSIBILITY	102 DB
DIFFUSION ANGLE	180°
1X 8" LOW & MEDIUM FREQUENCIES WOOFER	
1X 1" SILK DOME TWEETER	

CONNECTIVITY

APT X 4.0 BLUETOOTH
MINI-JACK 3,5MM
TRUE WIRELESS STEREO

VOODOO HI-FI PASSIVES



BASS REFLEX	CIRCULAR FRONT VENT
WAYS	2
SHELL MATERIAL	FLAX FIBER
WEIGHT	2 X 10 KG
DIMENSIONS	40 CM X 24 CM X 22 CM
DOUBLE TERMINAL COMPATIBLE SPEAKERS CABLES UNTIL 4 MM ²	
POWER	2 X 200 W RMS
FREQUENCY	40 TO 20 000 HZ
DISTORSION 90 DB LESS THAN 1 %	100 HZ TO 22 KHZ
SENSIBILITY	92 DB 1 W/1M
IMPEDANCE	4 OHMS
RECOMMENDED AMPLIFIER	DE 30 À 120 W RMS SOUS 4 OHMS
1X 8" LOW & MEDIUM FREQUENCIES WOOFER	
1X 1" SILK DOME TWEETER	

VOODOO HI-FI ACTIVE



BASS REFLEX	CIRCULAR FRONT VENT
WAYS	2
SHELL MATERIAL	FLAX FIBER
WEIGHT	2 X 10 KG
DIMENSIONS	40 CM X 24 CM X 22 CM
DOUBLE TERMINAL COMPATIBLE SPEAKERS CABLES UNTIL 4 MM ²	
POWER	2 X 200 W RMS
FREQUENCY	40 TO 20 000 HZ
DISTORSION 90 DB LESS THAN 1 %	100 HZ TO 22 KHZ
SENSIBILITY	92 DB 1 W/1M
IMPEDANCE	4 OHMS
RECOMMENDED AMPLIFIER	DE 30 À 120 W RMS SOUS 4 OHMS
1X 8" LOW & MEDIUM FREQUENCIES WOOFER	
1X 1" SILK DOME TWEETER	

CONNECTIVITY

BLUETOOTH APTX 4.0
MINI-JACK 3,5MM
TRUE WIRELESS STEREO